

Job Name:	Location:
Name:	Date:
Engineer:	Mechanical Operator:
Representative:	Type of Job: RNC <input type="checkbox"/> R&R <input type="checkbox"/> Commercial <input type="checkbox"/>
<input type="checkbox"/> Tstat Pro 9901-0010	Notes:

## TstatPro

### Residential/Commercial

Hardwire Only

CloudBeam and installer app available

Up to 2 heat, 3 cool conventional

Up to 5 heat, 3 cool heat pump

Occupancy override button

FDD Alarm input

Economizer Alarm In - displays on thermostat

Add up to 3 additional zones for extended control over pressure, temperature / humidity

Time based occupancy



## Application

The TstatPro is designed for single stage and multistage control of conventional and heat pump equipments. An embedded Web Server supports mobile phone or PC commissioning. When configured with an economizer you can program time based occupancy or use the occupancy override button. The Economizer FDD alarm output can be configured to annunciate on the front display.

# Specifications

Terminal Designations	Rc, Rh, G, Y, Y2, C, O, B, W/E, W2, D, H, S1 (DCV Out), S2 (Econ alm in)
Terminal Load Rating	1 amp per terminal, 1.5 amp maximum all terminals combined
Power Source	18 to 30 VAC, NEC Class II, 50/60 Hz for hardwire (common wire)
Display Range	41°F to 95°F (5°C to 35°C)
Control Range	44°F to 90°F (7°C to 32°C)
Display Accuracy	+/- 1°F
Cool Swing	Adjustable from 0.2°F to 2.0°F
Heat Swing	Adjustable from 0.2°F to 2.0°
Radio Communications	IEEE 802.b/g/n
FCC	FCC CFR 47 Part 15 Subpart B 6100A-CU300
Warranty	5 year warranty

Product	Part Number	Operating Ambient Temperatures	Operating Relative Humidity	Physical Dimensions (inches)
TstatPro	9901-0010	32° to 105° F (0°C to 41°C)	90% Non-Condensing Max	4.7L x 1.1W x 4.4H

# Measurements

